

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 1 of 12

SECTION 1 : IDENTIFICATION

1.1 Product identifier

Product name 8K Series Resin - RPG Resin, Smoke

Recommended use and restrictions on use

Recommended use For use in Phrozen 3D-printers

Restrictions on use Do not use in the situation that easily generate aerosol, steam.

1.2 Name, address and phone of manufacturer , importers or supplier

Manufacturer Phrozen Tech Co., Ltd. 287 Niupu Rd, Xiangshan Dist,
Hsinchu City 30091, TAIWAN(R.O.C)

Phone +886-3621-0505

Emergency phone / Fax +886-3621-0505 / +886-3539-6591

SECTION 2 : HAZARD IDENTIFICATION

2.1 Hazard classification

acute toxicity (oral) Category 4, Skin corrosion/irritation Category 2 ,

Serious eye damage/eye irritation Category 1 ,

Skin sensitization Category 1 , Specific target organ toxicity-repeated exposure Category 2

Hazardous to the aquatic environment (acute hazard) Category 1,

Hazardous to the aquatic environment (chronic hazard) Category 3,

2.2 Signal statement

Corrosion, Exclamation mark, Health hazard, Environment



2.3 Pictograms

2.4 Signal word Danger

2.5 Hazard statements

Causes skin irritation

Causes serious eye damage

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 2 of 12

Very toxic to aquatic life with long lasting effects

Harmful if swallowed.

2.6 Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read carefully and follow all instructions.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, If present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations.

2.7 Other hazard

None

SECTION 3 : COMPOSITION / INFORMATION ON INGREDIENTS

3.1. Substances

Not relevant (mixture)

3.2. Mixtures

Components	CAS number	Weight %	Classification acc. to GHS
4-(1-oxo-2-propenyl)-morpholine	5117-12-4	20 – 50%	Acute Tox. 4 / H302 Eye Dam. 1 / H318 Skin Sens. 1 / H317 STOT RE 2 / H373
Oxybis(methyl-2,1-ethanediyl) diacrylate	57472-68-1	10 – 25%	Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Eye Dam. 1 / H318
(2,4,6-trioxo-1,3,5-triazine 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate	40220-08-4	10 – 25%	Eye Dam. 1 / H318 Skin Sens. 1 / H317 Aquatic Chronic 2 / H411

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 3 of 12

4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3-epoxypropane, propane-1,2-diol acrylate and succinic anhydride	68958-77-0	10 – 25%	Acute Tox. 4 / H332 Skin Sens. 1B / H317 Aquatic Acute 1 / H400 Aquatic Chronic 4 / H413
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 1,6-diisocyanatohexane	264888-31-5	10 – 25%	Acute Tox. 4 / H302 Skin Sens. 1B / H317 Aquatic Chronic 3 / H412
Additives1	Trade Secret	2-5%	Aquatic Chronic 4 / H413
Additives2	Trade Secret	<1%	Carc. 2 / H351

SECTION 4 : FIRST AID MEASURES

4.1. First-aid advice and recommendations for different routes of exposure

4.1.1 Inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

4.1.2 Skin Contact

Wash with plenty of soap and water.

4.1.3 Eyes Contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, freshwater for at least 10 minutes, holding the eyelids apart.

4.1.4 Ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2. Most important symptoms and hazardous effects

None

4.3. Protection of First-aid personnel

None

4.4. Note for physician

None

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 4 of 12

SECTION 5 : FIRE-FIGHTING MEASURES

5.1 Applicable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

5.2 Specific hazards confronted during fire fighting

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Specific fire-fighting procedure

None

5.4 Specific protective equipments for fire-fighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2. Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3. Cleaning methods

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder. Covering of drains.

Place in appropriate containers for disposal. Ventilate affected area.

SECTION 7 : SAFETY HANDLING AND STORAGE

7.1. Handling

Use local and general ventilation. Use only in well-ventilated areas.

Do not eat, drink and smoke in work areas.

Remove contaminated clothing and protective equipment before entering eating areas.

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 5 of 12

Wash hands after use.

Never keep food or drink in the vicinity of chemicals.

Never place chemicals in containers that are normally used for food or drink.

7.2. Storage

Storage at the area of cool,dry.

Keep away from heat ,direct sunlight, rainy and rapid temperature .

Storage temperature between 15°C/ 59°C to 35°C / 95°F.

Close the lid tightly when not in use.

SECTION 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Engineering controls

Provide adequate ventilation to the areas where the product is stored and/or handled.

8.2. Control Parameters

Component	TWA	STEL	CEILING	BEI s
Titanium dioxide	10 mg / m ³	15 mg /m ³	-	-

8.3. Personal protective equipment

8.3.1 Respiratory protection

In case of inadequate ventilation wear respiratory protection.

8.3.2 Hand protection

Chemical protection gloves are suitable, which are tested according to EN 374.

For example : NBR: acrylonitrile-butadiene rubber

Material thickness : $\geq 0.6\text{mm}$

Breakthrough times of the glove material : > 480 minutes (permeation: level 6)

8.3.3 Eye protection

Use safety goggles.

8.3.4 Skin protection

Use clothing that provides complete protection to the skin.

8.4. Hygiene measures

Do not eat, drink and smoke in work areas.

Wash thoroughly after handling.

Keep clean of operation area.

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 6 of 12

Take off polluted clothing as soon as possible after work. The clothing can be re-wear only after washed in clean or discard.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Apperance and color	Smoke viscous liquid	Odor	Typical acrylate
Odor threshold	N/A	Melting point	N/A
pH value	6-8	Boiling point	104.5 °C at 2.05 hPa
Flammable	non-flammable	Flash point Testing method	>110°C Close up
Decomposition Temp	N/A		
Natural Temp	240°C	Explosive limit	N/A
Vapor pressure	0.5 hPa at 86.6 °C	Vapor density	N/A
Density	1.13 g /cm ³ at 25 °C	Solubility	insoluble in water
Octanol/water distribution coefficient (log Kow)	N/A	Evaporaion rate	N/A

SECTION 10: STABILITY AND REACTIVITY

10.1. Stability

Stable under normal condition.

10.2. Possible hazardous reation under specific conditions

None

10.3. Must avoid condition

UV-radiation/sunlight.

10.4. Must avoid substances

Oxidisers

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 7 of 12

10.5. Hazardous decomposed product

None

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Test data are not available for the complete mixture.

11.1. Exposure paths

None

11.2. Symptoms

None

11.3. Acute toxicity

Components	route	Value
4-(1-oxo-2-propenyl)-morpholine	Oral	588 mg/kg
4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3-epoxypropane, propane-1,2-diol acrylate and succinic anhydride	inhalation: vapour	11 mg/l /4h
	inhalation: dust/mist	4.9 mg/l /4h
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 1,6-diisocyanatohexane	Oral	≥2,000 mg/kg

11.4. Chronic toxicity

None

11.5. Reproductive and/or Developmental Effects

None

SECTION 12: ECOLOGICAL INFORMATION

The product has not been tested. The statement has been derived from the properties of the individual components.

12.1. Ecological toxicity

Aquatic toxicity (acute) of components of the mixture				
Components	End point	Value	Species	Exposure time
	LC50	4.64 mg/l	fish	96 h

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 8 of 12

Oxybis(methyl-2,1-ethane diyl) diacrylate	EC50	22.3 mg/l	aquatic invertebrates	48 h
	ErC50	16.7mg/l	algae	72h
4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3-epoxypropane, propane-1,2-diol acrylate and succinic anhydride	LL50	>100 mg/l	fish	96 h
	LC50	0.082mg/l	fish	96h
	EC50	>16mg/l	aquatic invertebrates	48h
	EL50	105mg/l	algae	48h
	ErC50	17mg/l	algae	72h
4-(1-oxo-2-propenyl)-morpholine	LC50	>220mg/l	fish	96h
	ErC50	>120mg/l	algae	96h
	EC50	230mg/l	algae	72h
(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate	LC50	9.43mg/l	fish	72 h
	EC50	158.3mg/l	aquatic invertebrates	48 h
	ErC50	25.7mg/l	algae	72h
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 1,6-diisocyanatohexane	EL50	58mg/L	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture

Components	End point	Value	Species	Exposure time
Oxybis(methyl-2,1-ethane diyl) diacrylate	EC50	>1,000 mg/l	microorganisms	30 min
4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3-epoxypropane, propane-1,2-diol acrylate and succinic anhydride	EC50	>1,000 mg/l	microorganisms	3h

12.2. Persistence and degradability

Degradability of components of the mixture				
Components	Process	Degradation rate	Time	Source
Oxybis(methyl-2,1-ethanediyl) diacrylate	DOC removal	90–100 %	28d	ECHA
4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3-epoxypropane	carbon dioxide generation	5%	29d	ECHA

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 9 of 12

e, propane-1,2-diol acrylate and succinic anhydride				
(2,4,6-trioxo-1,3,5-triazine 1,3,5(2H,4H,6H)-triy l)tri-2,1-ethanediyl triacrylate	oxygen depletion	19.7%	28d	ECHA
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 1,6-diisocyanatohexane	carbon dioxide generation	5%	28d	ECHA

12.3. Bio-accumulative potential

Components	BCF	Log kow	BOD/COD
Oxybis(methyl-2,1-ethanediyl) diacrylate		0.01- 0.39 (pHvalue : 7, 24°C)	
4-(1-oxo-2-propenyl)morpholine		0.01 – 0.39(pHvalue : 7, 23°C)	
4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3-epoxypropane, propane-1,2-diol acrylate and succinic anhydride		1.1(20.6°C)	
(2,4,6-trioxo-1,3,5-triazine 1,3,5(2H,4H,6H)-triy l)tri-2,1-ethanediyl triacrylate		1.09(pH value6.8,25°C)	
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 1,6-diisocyanatohexane		2.8-4.9(25°C)	-
[bis(4-methylphenyl) phosphoroso](2,4,6-trimethylphenyl)methanone		4.7(20°C)	

12.4. Mobility in soil

None

12.5. Other adverse effects

None

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 10 of 12

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste disposal methods

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

13.2. Sewage disposal method

Do not empty into drains. Avoid release to the environment.

13.3. Contaminated Packaging disposal method

Handle contaminated packages in the same way as the substance itself.

SECTION 14: TRANSPORT INFORMATION

Land transport USDOT	Not classified as dangerous goods under transport regulations.
Sea transport IMDG	Not classified as dangerous goods under transport regulations.
Air transport IATA/ICAO	Not classified as dangerous goods under transport regulations.
Further information	N/A
Other requirements	N/A

SECTION 15: REGULATORY INFORMATION

15.1. List of substances subject to authorisation (REACH, Annex XIV) / SVHC- candidate list

None of the ingredients are listed

15.2. Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

None of the ingredients are listed

15.3. Regulation concerning the establishment of a European Pollutant Release and

SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 11 of 12

Transfer Register (PRTR)

None of the ingredients are listed

15.4. Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

15.5. National inventories

Country	Inventory	Status
AU	AU AICS	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
DSL	Domestic Substances List (DSL)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
EU	EC Substance Inventory (EINECS, ELINCS, NLP)
EU	REACH registered substances
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
NZIoC	New Zealand Inventory of Chemicals
CICR	Chemical Inventory and Control Regulation
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act



SAFETY DATA SHEET

8K Series Resin - RPG Resin, Smoke

Page 12 of 12

SECTION 16: OTHER INFORMATION

Reference	US OSHA HCS 29 CFR 1910.1200
Table formulation unit	Name : Phrozen Tech. Co. Ltd Address / Phone : 287 Niupu Rd, Xiangshan Dist, Hsinchu City 30091, TAIWAN(R.O.C) /+ 886-3-6210505
Table formulator	Job title : Occupational Safety & Health manager Name : Chun-Yao, Kuo
Table formulation Date	2024.04.16
Remarks	In the above described information, the symbol "N/A" means no relevant information currently.

To the best of our knowledge the information contained herein is accurate. However, Phrozen Tech. Co. Ltd. makes no warranty, expressed or implied, regarding the accuracy of these results to be obtained from the use thereof. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Phrozen Tech. Co. Ltd. assumes no responsibility for injury from the use of the product described herein.

END OF SAFETY DATASHEET